

Version 18.0

| Build | Module | Description | ID |
|----------|-----------------|--|-------|
| 02.03.18 | Output document | The cpe-values for the automatically generated wind loads are now also issued. | 10513 |

Version 17.0

| Build | Module | Description | ID |
|----------|----------------|--|-------|
| 09.06.17 | User interface | Clicking onto the button „?...“ in the tab "Loading Options" no longer causes a program termination. | 11471 |
| 01.06.17 | Design | A wrong span length for the analysis was calculated with a missing negative deflection part in the span for girders with a cantilever. | 11441 |
| 11.01.17 | General | The design of girders made of the timber material Kerto-S is now possible. | 10285 |

Version 16.0

| Build | Module | Description | ID |
|----------|-------------|---|------|
| 05.04.16 | Calculation | The design in the case of fire according to 4.2.3 (reduced properties) is only intended for softwood according to DIN EN 1995-1-2/NA. With the adjustment to 4.2.2 (reduced cross-sections) for other types of wood also the cross-sections in the cold design were accidentally reduced with the minimum burn-off ratio $d_0 = 7$ mm in the program version 03/2016. | 9775 |
| 16.03.16 | General | The design of girders made of the timber material BauBuche GL70 (flat edge and on edge) is now possible. | 9731 |
| 12.01.16 | General | Program modifications for the compatibility with Windows 10 . | 9530 |

Version 15.0

| Build | Module | Description | ID |
|----------|-----------------|---|------|
| 13.11.15 | Evaluation | The buckling stability analysis was missing in the overview of the utilization. | 8215 |
| 03.06.15 | Output document | The admissible deflection was based on the field length instead of the actual span length when intermediate supports exist. | 9084 |
| 23.01.15 | General | Program maintenance and support | 8697 |

Version 14.0

| Build | Module | Description | ID |
|----------|---------|---------------------------------|------|
| 18.01.14 | General | Program maintenance and support | 7485 |

Version 13.0

| Build | Module | Description | ID |
|----------|----------------|--|------|
| 17.07.13 | Evaluation | The printout has been modified in the automatic calculation of the maximum overturning distances according to the "Kippfeldmethode". | 6883 |
| 17.07.13 | Evaluation | Some graphics were missing in the long printout. | 6882 |
| 15.03.13 | General | Now, the release notes are available in English . | 6453 |
| 15.03.13 | General | Program modifications for the compatibility with Windows 8 . | 6364 |
| 15.03.13 | User interface | When entering floating-point digits (Loads, intermediate supports, ...) a comma, and not only a point, is now accepted. | 4995 |